



Prox Key-Fob



Prox-Sticker



Prox Card (Thick)



Prox Card (Thin/ISO)

RFID/Prox Credentials

ZKAccess RFID/Prox credentials can be used with any ZKAccess readers which have a built-in 125 KHz prox card reader.

Note When ordering ZKAccess readers, be sure to specify which type card reader technology and credentials you need PRIOR to placing your order.

For customers already using existing non-ZKAccess card readers and cards, ZKAccess also provides 125 KHz key fobs which can be clipped on to existing customers' cards having a badge clip slot. And for customers having non-ZKAccess cards with no badge clip slot, we also offer 125 KHz self-adhesive RFID prox stickers.

Specifications

Interface

EM-4100 series prox cards with a EM/Marin S.A. memory chip.

125 KHz (generic prox)

26-bit, Read-only

13.56 MHz (Mifare)

Read-only

Passive prox/RFID responder

Dimensions

Key Fob size:

1.37 in x .91 in x .15 in
34.8 mm x 23mm x 3.9 mm

Prox Card Thick (clamshell)

Length: 3.36 in (85.47 mm)
Width: 2.12 in (53.85 mm)
Thickness: .077 in (1.97 mm)
Badge clip slot: 0.63 in X .13 in

RFID prox sticker size:

Diameter: 7/8 in (22.22 mm)
Thickness: 1/16 in (1.59 mm)

Prox Card Thin (ISO)

Length: 3.36 in (85.47 mm)
Width: 2.12 in (53.85 mm)
Thickness: 0.03 in (0.8 mm)
Badge clip slot: 0.63 in X 0.13 in
(16 mm X 3.30 mm)

Part Numbers

Prox Card Thick

Clamsheet-type card

Prox Card Thin

ISO-type card

Prox Key-Fob

Can be clipped on to keychain and pre-unched cards

Prox- Sticker

Self-adhesive backing sticks onto cards, phone, etc.

Design and Specifications subject to change without notice

ZKTeco USA

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004

Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com